



50° Incline Safety Angle Series

1-800-565-2165

Full Line Climbing & Access Products / Safety Angle Series

All-Directional Safety Angle (AD) (Patent Pending)

Construction & Features:

- The same construction and features as Heavy-Duty Safety Angle ladder
- 5-Wheels vs standard 4-wheels on all other rolling ladders
- All-Directional models equipped with swivel center casters enabling ladder to laterally maneuver



WLAD108246

Safety Angle and All-Directional Options

Stair Treads	Standard Feature	Optional Feature
Perforated	<input type="radio"/>	
Grip Strut	<input type="radio"/>	
Safety Walk		<input type="radio"/>

Top Step

27"	<input type="radio"/>
37"	<input type="radio"/>

Locking System

Step Lock	<input type="radio"/>
-----------	-----------------------

California OSHA Requirements

For more rigorous CAL-OSHA requirements for ladders with top platforms 50" and higher, the following parts are required to meet code: Contact us for pricing.

Part #	Models
C	7 – 16 steps

Perforated Tread

KD150	All-Welded
RWAD107246	WLAD107246
RWAD108246	WLAD108246
RWAD109246	WLAD109246
RWAD110246	WLAD110246
RWAD111246	WLAD111246
RWAD112246	WLAD112246
RWAD113246	N/A
RWAD114246	N/A
RWAD115246	N/A
RWAD116246	N/A

Grip Strut Tread

KD150	All-Welded
RWAD107242	WLAD107242
RWAD108242	WLAD108242
RWAD109242	WLAD109242
RWAD110242	WLAD110242
RWAD111242	WLAD111242
RWAD112242	WLAD112242
RWAD113242	N/A
RWAD114242	N/A
RWAD115242	N/A
RWAD116242	N/A

Steps	Step Width	Platform Height	H	D	W	Wt. (lbs.) Perforated	Wt. (lbs.) Grip Strut
7	24	70	100	74	34	166	175
8	24	80	110	82	34	186	196
9	24	90	120	91	34	210	222
10	24	100	130	99	34	230	243
11	24	110	140	107	34	251	265
12	24	120	150	116	34	270	286
13	24	130	166	124	39	288	305
14	24	140	176	133	39	305	323
15	24	150	186	141	39	322	342
16	24	160	196	149	42	348	369

H = Overall Height D = Overall Depth W = Overall Width