



# Specialty Rolling Series

1-800-565-2165

Full Line Climbing & Access Products / Specialty Rolling Series

## Roll & Fold (RF)

### Construction & Features:

- Same construction as Steel Rolling Ladder
- Rolls on two 10" x 1 3/4" semi-pneumatic wheels for use on all types of floors
- Crutch tips on front legs help keep ladder in place
- Standard Perforated or Grip Strut™ tread design
- 450 lb. rated capacity



RWRF106166

### Roll & Fold and Tilt & Roll Options

	Standard Feature	Optional Feature
<b>Stair Treads</b>		
Perforated	<input type="radio"/>	
Grip Strut	<input type="radio"/>	
Safety Walk		<input type="radio"/>
<b>Top Step</b>		
10"	<input type="radio"/>	
20"		<input type="radio"/>
30"		<input type="radio"/>
<b>Shelf</b>		
Hanging Shelf		<input type="radio"/>

### California OSHA Requirements (RF and TF)

For more rigorous CAL-OSHA requirements for ladders with top platforms 50" and higher, the following parts are required to meet code: Contact us for pricing.

Part #	Models
C	5 - 12 steps

Steps	Step Width	Platform Height	KD150			W	Wt. (lbs.) Perforated	Wt. (lbs.) Grip Strut	
			H	D	H				
RWRF103166	RWRF103162	3	16	30	60	27	20	45	49
RWRF104166	RWRF104162	4	16	40	70	35	23	65	70
RWRF105166	RWRF105162	5	16	50	80	42	23	71	78
RWRF106166	RWRF106162	6	16	60	90	50	27	84	92
RWRF107166	RWRF107162	7	16	70	100	57	27	97	103
RWRF108166	RWRF108162	8	16	80	112	63	34	110	120
RWRF109166	RWRF109162	9	16	90	122	70	34	123	135
RWRF110166	RWRF110162	10	16	100	132	77	34	138	151
RWRF111166	RWRF111162	11	16	110	142	83	34	154	168
RWRF112166	RWRF112162	12	16	120	152	90	34	170	186

H = Overall Height    D = Overall Depth    W = Overall Width

## Tilt & Roll (TF)

COMING SOON! New knock down Tilt & Roll design

### Construction & Features:

- Same construction as Steel Rolling Ladder
- Standard Perforated or Grip Strut™ tread design
- Ladder tilts onto two 4" casters for easy transport from job to job
- Four rubber tips help keep ladder secure to the floor
- 450 lb. rated capacity
- Optional 20" or 30" deep top platform
- Optional Safety Walk tread



WLTF104246

Steps	Step Width	Platform Height	All-Welded			W	Wt. (lbs.) Perforated	Wt. (lbs.) Grip Strut	
			H	D	H				
WLTF102166	WLTF102162	2	16	20	50	19	20	35	38
WLTF102246	WLTF102242	2	24	20	50	19	28	41	43
WLTF103166	WLTF103162	3	16	30	60	27	20	45	49
WLTF103246	WLTF103242	3	24	30	60	27	28	52	62
WLTF104166	WLTF104162	4	16	40	70	35	23	55	73
WLTF104246	WLTF104242	4	24	40	70	35	31	63	68
WLTF105166	WLTF105162	5	16	50	80	42	23	64	75
WLTF105246	WLTF105242	5	24	50	80	42	31	80	85
WLTF106166	WLTF106162	6	16	60	90	50	27	74	82
WLTF106246	WLTF106242	6	24	60	90	50	34	97	104
WLTF107166	WLTF107162	7	16	70	100	57	27	84	92
WLTF107246	WLTF107242	7	24	70	100	57	34	114	122

H = Overall Height    D = Overall Depth    W = Overall Width